

同 C E X of Conformity Certificate

INTERNATIONAL IEC Certification Scheme for Explosive Atmospheres **ELECTROTECHNICAL COMMISSION**

for rules and details of the IECEx Scheme visit www.iecex.com

Status:	Certificate No.:
Current	IECEx BAS 08.0028X
	issue No.:2

Certificate history: Issue No. 2 (2012-12-6) Issue No. 1 (2008-11-6) Issue No. 0 (2008-9-17)

Date of Issue: 2012-12-06

Page 1 of 4

Applicant:

Crowcon Detection Instruments Ltd 2 Blacklands Way Abingdon Business Park Abingdon Oxfordshire OX14 1DY

United Kingdom

Electrical Apparatus: Optional accessory:

TXgard-IS+

Type of Protection:

Intrinsic Safety ia

Marking:

Ex ia IIC T4 Ga (-40°C to +65°C)

Approved for issue on behalf of the IECEx Certification Body:

R S Sjóckáir

Position:

Signature: (for printed version)

Date:

heral Manager

This certificate and schedule may only be reproduced in full.
 This certificate is not transferable and remains the property of the issuing body.
 The Status and authenticity of this certificate may be verified by visiting the Official IECEx Website.

Certificate issued by:

Rockhead Business Park SGS Baseefa Limited Staden Lane Buxton Derbyshire SK17 9RZ

United Kingdom





ECEx Certificate Conformity

Certificate No.:

IECEx BAS 08.0028X

Date of Issue:

Issue No.: 2

Page 2 of 4

Manufacturer:

Crowcon Detection Instruments Limited2 Blacklands Way
Abingdon Business Park
Abingdon

Oxfordshire OX14 1DY

United Kingdom

Manufacturing location(s):

This certificate is issued as verification that a sample(s), representative of production, was assessed and tested and found to comply with the IEC Standard list below and that the manufacturer's quality system, relating to the Ex products covered by this certificate, was assessed and found to comply with the IECEx Quality system requirements. This certificate is granted subject to the conditions as set out in IECEx Scheme Rules, IECEx 02 and Operational Documents as amended.

STANDARDS:

The electrical apparatus and any acceptable variations to it specified in the schedule of this certificate and the identified documents, was found to comply with the following standards:

Edition: 6.0 IEC 60079-0 : 2011

Explosive atmospheres - Part 0: General requirements

IEC 60079-11 : 2011-

Explosive atmospheres - Part 11: Equipment protection by intrinsic safety "i"

IEC 60079-26: 2006

Edition: 6.0

Explosive atmospheres - Part 26: Equipment with equipment protection level (EPL) Ga

This Certificate **does not** indicate compliance with electrical safety and performance requirements other than those expressly included in the Standards listed above.

TEST & ASSESSMENT REPORTS:

A sample(s) of the equipment listed has successfully met the examination and test requirements as recorded in

Test Report: GB/BAS/ExTR08.0063/00

GB/BAS/ExTR08.0122/00

GB/BAS/ExTR12.0316/00

Quality Assessment Report:

GB/BAS/QAR06.0070/03



ECEX Conformity Certificate

Certificate No.:

IECEx BAS 08.0028X

Date of Issue:

2012-12-06

Issue No.: 2

Page 3 of 4

Schedule

EQUIPMENT:Equipment and systems covered by this certificate are as follows:

The TXgard-IS+ is a gas detector capable of detecting a wide range of non-combustible gasses. The sensor which is in a housing attached to the side of the TXgard-IS+ determines the gas types that the apparatus will detect. The Personality Module inside the detector is either an Oxygen Personality Module that is specific to the oxygen detecting variant, or is a Toxic Gas Personality Module that is common to all toxic gas detecting variants. Calibration and the selection of different features is carried out via a three button keypad and external LCD. The detector uses a two terminal 4-20mA loop for power input and signal output.

⊐
0
Č
_
_
_U
α
~
₩.
3
<u></u>
*
Œ
77
S

__ **28V**

_ □ -93mA ت_ ي 11 11 0 0

П 0.66W

CONDITIONS OF CERTIFICATION: YES as shown below:

	-
	_
	0
	₹
	⊒
	3
	Z
	e
	=
	S
	9
	æ
	ē
	2
	000
	6
	5
	0
	Š
	ĭ
	H
	ĕ
	5
	æ
	a
	30
	a
	2
	S
	₹
	Š
	0
:0	₹
	0
	ĕ
	ë
	ä
	ĕ
	2
	ŝ
	Ξ
	0
	0
	H
	5
	S
	5



ECEx Certificate of Conformity

Certificate No.:

IECEx BAS 08.0028X

Date of Issue:

2012-12-06

Issue No.: 2

Page 4 of 4

DETAILS OF CERTIFICATE CHANGES (for issues 1 and above):

Variation 2.1

To permit a minor label change not affecting the original assessment.

Variation 2.2

To confirm the current design of the TXgard-IS+ has been reviewed against the requirements of IEC 60079-0: 2011 Edition 6 and IEC 60079-11: 2011 Edition 6 in respect of the differences from IEC 60079-0: 2007 Edition 5 and IEC 60079-11: 2006 Edition 5 and none of the differences affect the equipment.

EXTR: GB/BAS/EXTR12.0316/00 File Reference: 12/0885



IECEx Certificate of Conformity

INTERNATIONAL IEC Certification Scheme for Explosive Atmospheres **ELECTROTECHNICAL COMMISSION**

for rules and details of the IECEx Scheme visit www.iecex.com

Certificate No.: IECEx BAS 08,0028X

issue No.:1

Certificate history: Issue No. 1 (2008-11-6) Issue No. 0 (2008-9-17)

Current

Date of Issue:

Status:

2008-11-06

Page 1 of 4

Applicant:

Crowcon Detection Instruments Ltd 2 Blacklands Way Abingdon Business Park Abingdon Oxfordshire OX14 1DY

United Kingdom

Electrical Apparatus: Optional accessory:

TXgard-IS+

Type of Protection:

Intrinsic Safety ia

Marking:

Ex ia IIC T4 Ga (-40°C to +65°C)

Approved for issue on behalf of the IECEX Certification Body:

R S Sinclair

Position:

Signature: (for printed version)

Managing Director

Date:

This certificate and schedule may only be reproduced in full.
 This certificate is not transferable and remains the property of the issuing body.
 The Status and authenticity of this certificate may be verified by visiting the Official IECEx Website.

Certificate issued by:

Baseefa Rockhead Business Park Staden Lane **United Kingdom** Derbyshire SK17 9RZ Buxton





ECEx Certificate Conformity

Certificate No.:

Date of Issue:

IECEx BAS 08.0028X

2008-11-06

Issue No.: 1

Manufacturer:

Page 2 of 4

Crowcon Detection Instruments Limited 2 Blacklands Way Abingdon Business Park Abingdon Oxfordshire OX14 1DY United Kingdom

Manufacturing location(s):

This certificate is issued as verification that a sample(s), representative of production, was assessed and tested and found to comply with the IEC Standard list below and that the manufacturer's quality system, relating to the Ex products covered by this certificate, was assessed and found to comply with the IECEx Quality system requirements. This certificate is granted subject to the conditions as set out in IECEx Scheme Rules, IECEx 02 and Operational Documents as amended.

STANDARDS:

The electrical apparatus and any acceptable variations to it specified in the schedule of this certificate and the identified documents, was found to comply with the following standards:

IEC 60079-0 : 2004 Edition: 4.0 Electrical apparatus for explosive gas atmospheres - Part 0: General requirements

IEC 60079-11 : 2006 Edition: 5 Explosive atmospheres - Part 11: Equipment protection by intrinsic safety "i"

IEC 60079-26: 2006

Explosive atmospheres - Part 26: Equipment with equipment protection level (EPL) Ga

Edition: 2

This Certificate does not indicate compliance with electrical safety and performance requirements other than those expressly included in the Standards listed above.

TEST & ASSESSMENT REPORTS:
A sample(s) of the equipment listed has successfully met the examination and test requirements as recorded in

GB/BAS/ExTR08.0063/00 GB/BAS/ExTR08.0122/00

GB/BAS/QAR06,0070/00



ECEx Certificate of Conformity

Certificate No.:

IECEx BAS 08.0028X

Date of Issue:

2008-11-06

Issue No.: 1

Page 3 of 4

Schedule

EQUIPMENT:
Equipment and systems covered by this certificate are as follows:

The TXgard-IS+ is a gas detector capable of detecting a wide range of non-combustible gasses. The sensor which is in a housing attached to the side of the TXgard-IS+ determines the gas types that the apparatus will detect. The Personality Module inside the detector is either an Oxygen Personality Module that is specific to the oxygen detecting variant, or is a Toxic Gas Personality Module that is common to all toxic gas detecting variants. Calibration and the selection of different features is carried out via a three button keypad and external LCD. The detector uses a two terminal 4-20mA loop for power input and signal output.

CONDITIONS OF CERTIFICATION: YES as shown below:

To minimize the risk of electrostatic discharge the apparatus must only be cleaned using a damp cloth.



of Conformity

Certificate No.:

IECEx BAS 08.0028X

Date of Issue:

2008-11-06

Issue No.: 1

Page 4 of 4

DETAILS OF CERTIFICATE CHANGES (for issues 1 and above):

Variation 1.1

To permit minor electrical and mechanical changes that do not affect the existing assessment.

EXTR: GB/BAS/EXTR08.0122/00

File Reference: 08/0736



IECEx Certificate of Conformity

INTERNATIONAL ELECTROTECHNICAL COMMISSION IEC Certification Scheme for Explosive Atmospheres for rules and details of the IECEx Scheme visit www.iecex.com

Certificate No.: IECEx BAS 08.0028X

Status:

Current

issue No.:0

Certificate history:

Date of Issue:

2008-09-17

Applicant:

Crowcon Detection Instruments Limited 2 Blacklands Way Abingdon Business Park Abingdon Oxfordshire OX14 1DY United Kingdom

Electrical Apparatus: Optional accessory:

TXgard-IS+

Type of Protection:

Intrinsic Safety la

Marking:

Ex la IIC T4 Ga (-40°C to +65°C)

R S Sinclair

Approved for issue on behalf of the IECEX Certification Body:

Position:

Managing Director

Signature: (for printed version)

Date:

100

This certificate and schedule may only be reproduced in full.
 This certificate is not transferable and remains the property of the issuing body.
 The Status and authenticity of this certificate may be verified by visiting the Official IECEx Website.

Certificate issued by:

Baseefa
Rockhead Business Park
Staden Lane
Buxton
Derbyshire
SK17 9RZ
United Kingdom





ECEx Certificate of Conformity

Certificate No.:

IECEx BAS 08.0028X

Date of Issue:

2008-09-17

Issue No.: 0

Page 2 of 3

Manufacturer:

Crowcon Detection Instruments Limited 2 Blacklands Way Abingdon Business Park Abingdon Oxfordshire OX14 1DY United Kingdom

Manufacturing location(s):

This certificate is issued as verification that a sample(s), representative of production, was assessed and tested and found to comply with the IEC Standard list below and that the manufacturer's quality system, relating to the Ex products covered by this certificate, was assessed and found to comply with the IECEx Quality system requirements. This certificate is granted subject to the conditions as set out in IECEx Scheme Rules, IECEx 02 and Operational Documents as amended.

STANDARDS:

The electrical apparatus and any acceptable variations to it specified in the schedule of this certificate and the identified documents, was found to comply with the following standards:

IEC 60079-0: 2004 Edition: 4.0 IEC 60079-11: 2006 Edition: 5

Electrical apparatus for explosive gas atmospheres - Part 0: General requirements

Explosive atmospheres - Part 11: Equipment protection by intrinsic safety "i"

IEC 60079-26 : 2008 Edition: 2

Explosive atmospheres - Part 26: Equipment with equipment protection level (EPL) Ga

This Certificate does not indicate compliance with electrical safety and performance requirements other than those expressly included in the Standards listed above.

TEST & ASSESSMENT REPORTS: A sample(s) of the equipment listed has successfully met the examination and test requirements as recorded in

Test Report:

GB/BAS/ExTR08.0063/00

Quality Assessment Report: GB/BAS/QAR06.0070/00



IECEx Certificate of Conformity

Certificate No.:

IECEX BAS 08.0028X

Date of Issue:

2008-09-17

Issue No.: 0

Page 3 of 3

Schedule

EQUIPMENT:
Equipment and systems covered by this certificate are as follows:

The TXgard-IS+ is a gas detector capable of detecting a wide range of non-combustible gasses. The sensor which is in a housing attached to the side of the TXgard-IS+ determines the gas types that the apparatus will detect. The Personality Module inside the detector is either an Oxygen Personality Module that is specific to the oxygen detecting variant, or is a Toxic Gas Personality Module that is common to all toxic gas detecting variants. Calibration and the selection of different features is carried out via a three button keypad and external LCD. The detector uses a two terminal 4-20mA loop for power input and signal output.

CONDITIONS OF CERTIFICATION: YES as shown below:

1. To minimize the risk of electrostatic discharge the apparatus must only be cleaned using a damp cloth.